

# Julie

## IP65 LED luminaire



### Meet Julie

With a tough exterior, Julie is the optimal choice for industrial and commercial applications

- High quality, low energy lighting in wet and dusty environments
- High quality opal diffuser for uniform lighting
- Ideal for replacement and refurbishment projects
- 4000 lm (40 W), 6000 lm (60 W), up to 100 lm/W
- Colour Temperature 4000 K



**IP65:**  
Dust tight and water resistant



Save up to 60% energy compared to T8 fluorescent



**IK08 rated**  
impact resistance



Lengths of 1232 mm and 1532 mm



2h emergency version available



50 000 hours lifetime

### Ideal for...



Car parks



Workshops



Underpasses



Storage facilities

### Installation/Mounting

Suitable for surface mounting. 4 x 10 mm stainless steel self-tapping screws (not included) can be applied to prevent unauthorised opening of the luminaire.

### Material/Finish

Canopy: Polycarbonate  
Diffuser: Opal polycarbonate  
Bracket: Stainless steel


### Specification

- Class I electrical
- IP65
- IK08
- Ambient operating temperature: -20 to +40°C STD, 0 to +25°C EL2



L B H

JULIE 1200 LED IP65 4000	1232	103	78
JULIE 1500 LED IP65 6000	1532	103	78




## Lighting distribution

Julie LED 6000lm

cd/klm ULOR: 8% DLOR: 92% LOR: 100%

100lm/W 



## Ordering guide

Description	Wt (kg)	SAP Code
JULIE 1200 LED IP65 4000 840	1.50	96665577
JULIE 1500 LED IP65 6000 840	1.95	96665580
<b>Emergency versions</b>		
JULIE 1200 LED IP65 4000 840 EL2*	1.90	96646833
<b>Spare part</b>		
JULIE LED Spare Mount Kit		96628409

\*AS 2293 Emergency Classification  
C0 = D40, C90 = D25  
2 Hour Maintained, LED Emergency Luminaire

## Light source information

- Life time 50 000 hours (@L70B50, Ta 25°C)
- 4000lm (40 W), 6000lm (60 W), up to 100lm/W
- Colour temperature 4000 K
- CRI80
- McAdams (initial): 4 step

