Alice

LED floodlight

Meet Alice

Both strong and bright, Alice is robust and reliable no matter the weather

- 5 different lumen packages from 10 W to 100 W
- Very lightweight, compact and streamline design
- Universal mounting bracket allows wall or surface mounting with the possibility of tilting upwards or downwards
- Pre-wired with mains cable





800, 1600, 2400, 4000 and 8000 lumens

Save up to 70% energy compared with halogen floodlights






Sealed to IP65 for protected exterior applications

Ideal for...

Gardens

IK08 rated impact resistance








• 800 lm (10 W), 80 lm/W, 1600 lm (20 W), 80lm/W, 2400lm (30W), 80lm/W, 4000lm (50W), 80lm/W, 8000lm (100W), 80lm/W

Car parks


Building facades

- 4000K neutral white LED
- Lifetime: 35 000 hour rated life (@L70B50, Ta 25 °C)
- CRI80





L	W	H1	H2
130	26	126	92
180	31	169	130
180	31	169	130
290	41	270	208
360	42	331	268
	180 180 290	130 26 180 31 180 31 290 41	130 26 126 180 31 169 180 31 169 290 41 270



Performance guide

Description	Lumen output	Alternative to Halogen	Alternative to Discharge
ALICE LED 10W	800 lm	50 W	
ALICE LED 20W	1600 lm	100W	
ALICE LED 30W	2400 lm	150W	
ALICE LED 50W	4000 lm	250W	70 W
ALICE LED 100W	8000 lm	400W	150W

The above table is a guide for replacement of traditional floodlights, using the closest LED alternative offer.

Ordering guide

Description	Wt (kg)	Cat. No.
ALICE LED FL IP65 10 W 840	0.4	AC10W
ALICE LED FL IP65 20W 840	0.75	AC20W
ALICE LED FL IP65 30W 840	0.75	AC30W
ALICE LED FL IP65 50W 840	2.45	AC50W
ALICE LED FL IP65 100 W 840	3.8	AC100W

Installation/Mounting

- Suitable for wall or ceiling mounting
- Pre-wired with mains cable and open cable ends with 1mm² cross section. 100 cm cable for 50 & 100 W flood-lights and 30 cm cable for 10, 20 & 30 W floodlights

Material/Finish

Glass: Tempered glass Reflector: Aluminum Quick and easy installation Body: Aluminum die-cast Screws: Stainless steel



Specification

- Class I electrical
- IP65
- IK08