

Mike



also known as
Mr. Minilux
LED batten

Meet Mike

A reliable and compact LED batten, Mike helps provide an ambient environment

- Shadow free continuous light thanks to well designed end caps
- High quality diffuser ensures uniform light without visible spots
- Can be individual or continuous mounted
- Supplied complete with starter lead, mounting kit, connector lead and interconnector



900 lm and
1800 lm, up to
90 lm/W



40% energy
savings
compared to
T5 fluorescent



1170 mm
(1800 lm) and
570 mm
(900 lm)

Ideal for...



Cove lighting




Cabinet lighting



Residential

Light source information


- Lifetime 35 000 hours (@L70B50, Ta 25 °C)
- 900 lm (10 W), 1800 lm (18 W), 90 lm/W @ 4000 K
- Colour temperature 3000 K, 4000 K
- CRI 80
- McAdams (initial): 5 step



Lighting distribution

Mike alias Minilux LED II 1170 mm 1800 lm
cd/klm ULOR: 23% DLOR: 77% LOR: 100%

90 lIm/W 



Ordering guide

Description	Wt (kg)	SAP Code
Mike MINILUX2 LED900-L830 HF L570	0.17	96644485
Mike MINILUX2 LED900-L840 HF L570	0.17	96644486
Mike MINILUX2 LED1800-L830 HF L1170	0.29	96644483
Mike MINILUX2 LED1800-L840 HF L1170	0.29	96644484
Spare part		
Mike MINILUX2 LED Spare Mount Kit		96628411

830-3000 K, 840-4000 K

Installation/Mounting

- Suitable for surface mounting.
- The fitting can be mounted individually or continuously (max. 10 battens).

Material/Finish

Body and diffuser: Dual-color extruded polycarbonate
End cap: Opal polycarbonate

Specification

- Class I electrical
- IP20
- IK02