

# Mike

also known as  
Mr. Minilux  
LED batten



## Meet Mike

A reliable and compact LED batten, Mike helps provide an ambient environment

- Shadow free continuous light thanks to well designed end caps
- High quality diffuser ensures uniform light without visible spots
- Can be individual or continuous mounted
- Supplied complete with starter lead, mounting kit, connector lead and interconnector



900 lm and  
1800 lm, up  
to 90 lm/W



40 % energy  
savings  
compared  
to T5  
fluorescent



1170 mm  
(1800 lm) and  
570 mm  
(900 lm)

### Ideal for...



Cove  
lighting



Cabinet  
lighting



Residential

### Light source information


- Lifetime 35 000 hours (@L70B50, Ta 25° C)
- 900 lm (10 W), 1800 lm (18 W), 90 lm/W @ 4000 K
- Colour temperature 3000 K, 4000 K
- CRI 80
- McAdams (initial): 5 step



## Lighting distribution

Mike alias Minilux LED II 1170 mm 1800 lm  
cd/klm ULOR: 23% DLOR: 77% LOR: 100%

90lm/W



### Installation/Mounting

- Suitable for surface mounting.
- The fitting can be mounted individually or continuously (max. 10 battens).

### Material/Finish

Body and diffuser: Dual-color extruded polycarbonate

End cap: Opal polycarbonate

### Specification

- Class I electrical
- IP20
- IK02

## Ordering guide

Description	Wt (Kg)	SAP Code
Mike MINILUX2 LED900-L830 HF L570	0.17	96644485
Mike MINILUX2 LED900-L840 HF L570	0.17	96644486
Mike MINILUX2 LED1800-L830 HF L1170	0.29	96644483
Mike MINILUX2 LED1800-L840 HF L1170	0.29	96644484
<b>Spare part</b>		
Mike MINILUX2 LED Spare Mount Kit		96628411

830-3000K, 840-4000K

