

Anna

Recessed LED Panel




Meet Anna

Low glare and calm,
Anna is the universal
talent for desk space
environments

- Gentle, soft and glare free lighting (UGR <19) thanks to a Light Guide Plate with innovative laser engraving
- Smooth opal diffuser for fully homogeneous illumination
- Even surface and IP44 (from below) for hassle-free cleaning
- Elegant and timeless design with slim metal frame of only 8.5 mm depth
- Replaces conventional luminaires with 4x18 W T8 and offers up to 60% energy saving
- Easy, quick and tool-free installation thanks to an external connector box with a 4-pole push-terminal (for up to 2.5 mm² wires) enabling loop-in loop-out wiring
- The fully detachable connector allows for first fix wiring and high voltage circuit testing whilst the luminaire is detached from the connector

THORN
eco



3500 lumens
106 lm/W
(4000K) and
3200 lumens
97 lm/W
(3000K)



IP44
(from below):
Splash
resistant for
hassle-free
cleaning



UGR <19:
gentle, soft
and glare-free
lighting for
office
applications



596 x 596 mm
and
622 x 622 mm



3h emergency
version
available



50 000 hours
lifetime

Ideal for...




Offices and
meeting rooms



Schools and
universities

Light source information

- 4000 K, 3500 lm (33 W), 106 lm/W
- 3000 K, 3200 lm (33 W), 97 lm/W
- 50 000 hour rated life (@L70B50, T_a 25°C)
- CRI 80
- McAdam (initial): 4 step
- UGR <19




Lighting distribution

Anna 3500lm

cd/klm ULOR: 0% DLOR: 100% LOR: 100%

106lm/W



Ordering guide

Description	Wt (kg)	SAP Code
ANNA LED Q596 3500 840	3.3	96630066
ANNA LED Q622 3500 840	3.3	96630067
ANNA LED Q596 3200 830	3.5	96630069
ANNA LED Q622 3200 830	3.5	96630070
Emergency version		
ANNA LED Q596 3500 840 E3	3.9	96630068
Accessories		
ANNA Q596 Recessed Mount Box		96630224
ANNA Q622 Recessed Mount Box		96630225
ANNA Q596 Slim Surface Mount Box		96630226
ANNA Q622 Slim Surface Mount Box		96630227
ANNA Suspension Kit		96630223

830-3000K, 840-4000K

Installation/Mounting

- Lay-in installation in T-bar ceiling grids
- Suitable for suspension, surface and recessed installation

Material/Finish

Frame: Aluminum, white (RAL 9003)
 Diffuser: PET, opal (TpB rated)
 Light guide plate: PS
 Backplate: Steel sheet

Specification

- Class II electrical
- IP44 (from below), IP20 (from above)
- IK02
- ENEC certified driver

