

# Fred

## Fire-rated LED Downlight



### Meet Fred

Brave and solid, Fred is a fire-rated everyday hero

- Recessed IP65 fire-rated downlight, including white bezel and lens with 38° beam angle
- Highly efficient and economical downlight, fully fire-rated for 30, 60 & 90 minute ceilings
- Easily exchangeable bezels: swap white with chrome, satin chrome or bronze (available as accessories)
- Adapt the light distribution by exchanging the 38° lens with a 24°/46° beam angle lens or a 15° wall wash optic (available as accessories)
- The fully detachable connector allows for first fix wiring and high voltage circuit testing whilst the luminaire is detached from the connector
- Tool free and fast wiring thanks to the press-fit terminal block enabling convenient loop-in loop-out
- Groove heatsink design for ideal dissipation of heat
- Integrated LED driver suitable for use with leading-edge dimmer switches from approved manufacturers
- Suitable for use in bathrooms
- Ideal one to one replacement for 35W halogen downlights and up to 90% energy saving



550 lumens at  
80 lm/W



50 000 hours  
lifetime



Dimmable



IP65 (from  
below):  
Dust tight  
and water  
resistant



Fully fire-  
rated for 30,  
60 and 90  
minute ceilings



3000 K  
warm white or  
4000 K  
neutral white

### Ideal for...



Retail shops




Schools and  
universities



Hotels

### Light source information

- 550lm (7W); 80lm/W
- Color temperature 3000K and 4000 K
- Life time 50 000 hours (@L70, Ta 25°C)
- CRI ≥80
- McAdam (initial): 6 step




## Lighting distribution

### Fred 550lm

cd/klm ULOR: 0% DLOR: 100% LOR: 100%

80lm/W



## Ordering guide

Description	Wt (kg)	SAP Code
FRED LED IP65 75 550 840	0.3	96630340
FRED LED IP65 75 550 830	0.3	96630341
<b>Accessories</b>		
FRED TRIM CHR	0.5	96630345
FRED TRIM SAT	0.5	96630346
FRED TRIM BRO	0.5	96630390
FRED TRIM GLOSSY WH	0.5	96630573
FRED TRIM MATT BLK	0.5	96630574
FRED LENS 24°	0.01	96630347
FRED LENS 46°	0.01	96630349
FRED LENS 15° WALL WASH	0.01	96630391
★ FRED Connector	0.05	96631529
<b>Spare parts</b>		
FRED LENS 38°	0.01	96630348
FRED TRIM MATT WH	0.5	96630344

★ New

### Installation/Mounting

- Fred fire-rated downlight can be installed into a wide range of ceiling types
- Mineral wool insulation can be placed directly over the top of the fitting

### Material/Finish

Body: Aluminum heat sink & steel housing  
 Bezel trim: Aluminum die-cast, matt white  
 Lens: PMMA  
 Cover: PC

### Specification

- Class II electrical
- IP65 (from below), IP20 (from above)
- IK04

