

Leo

High Power LED Floodlight



Meet Leo

Extremely powerful and resilient, Leo adds safety to dark areas

- 5 different lumen packages from 7500 to 25000 lm
- Asymmetrical light distribution – ideal for building facades and footpaths
- Integrated photocell for automatic light from dusk til dawn (can be activated/deactivated)
- Compact and streamline design
- Universal mounting bracket allows wall or ceiling mounting with the possibility of tilting upwards or downwards
- Surge protection up to 10 kV to protect the product from short high voltage spikes caused e.g. by a lightning storm
- Climate membrane for automatic climate regulation inside the floodlight
- Pre-wired with mains cable (3m)



7500, 10000, 15000, 20000 and 25000 lumens



Sealed to IP66 for exterior applications



Save up to 70% energy compared with halogen floodlights



IK08 rated impact resistance



50 000 hours lifetime



Integral photocell

Ideal for...



Building facades



Car Parks



Footpaths



Loading bays


Light source information

- 7500 lm (75 W), 10000 lm (100 W), 15000 lm (150 W), 20000 lm (200 W), 100 lm/W
- 25000 lm (210 W), 120 lm/W
- Color temperature 3000K and 4000K
- Life time 50000 hours (@L70, Ta 25 °C)
- CRI ≥ 80
- MacAdam (initial): 5 step
- Beam angle: 100 × 55°

Specification

- Class I electrical
- IP66
- IK08
- Ambient operating temperature: -20 to +50 °C


	L	W	H
LEO LED FL IP66 75W 840	272	67	347
LEO LED FL IP66 100W 840	272	67	347
LEO LED FL IP66 150W 840	366	72	456
LEO LED FL IP66 200W 840	366	72	456
LEO LED FL IP66 210W 840	366	72	456



Lighting distribution

Leo 15 000lm

cd/klm ULOR: 0 % DLOR: 100 % LOR: 100 %



Ordering guide

Description	Wt (kg)	SAP Code
★ LEO LED FL IP66 75W 830 PC	4.1	96632698
LEO LED FL IP66 75W 840 PC	4.1	96630252
★ LEO LED FL IP66 100W 830 PC	4.2	96632699
LEO LED FL IP66 100W 840 PC	4.2	96630253
★ LEO LED FL IP66 150W 830 PC	6.6	96632700
LEO LED FL IP66 150W 840 PC	6.6	96630254
★ LEO LED FL IP66 200W 830 PC	6.6	96632701
LEO LED FL IP66 200W 840 PC	6.6	96630255
★ LEO LED FL IP66 210W 830 PC	6.6	96632702
LEO LED FL IP66 210W 840 PC	6.6	96630256

★ New

Installation/Mounting

- Suitable for wall or ceiling mounting
- Quick and easy installation thank to universal mounting bracket (0-300°)
- Pre-wired with 3 m long mains cable and open cable ends with 1mm² cross section

Material/Finish

Body: Aluminum die-cast (<5% copper)
 Bracket: Carbon steel, gray (RAL 9006)
 Cover: Tempered glass
 Lens: PC

Integral photocell

Leo's integral photocell can easily be activated/deactivated by using the on/off switch on the back of the product. If the photocell is activated, Leo will automatically light from dusk til dawn. (Operation level: approx. 20lux ON, 75lux OFF)



Five year guarantee