

Lucy

LED Batten

New

Meet Lucy

Tough, resilient and efficient, Lucy is ideal for workshop areas and functional applications

- High quality, low energy lighting in wet and dusty environments with opal diffuser for uniform lighting
- 2000 lm (20 W), 4000 lm (40 W), 6000 lm (60 W), 8000 lm (80 W), 100 lm/W
- Through-wired: equipped with two 3-pole push-terminals (N, earth, L) as standard
- Easy, quick and tool-free installation thanks to the twist & lock mechanism in the end caps, which allowing access to the push terminals
- Flexible installation as mounting brackets can be positioned freely on the luminaire



IP66:
Dust tight
and water
resistant



IK08 rated
impact
resistance



Save up
to 60%
compared to
T8 fluorescent



600 mm,
1200 mm,
1500 mm and
1800 mm



Through-wired



Tool free
installation

Ideal for...



Car parks



Workshops



Underpasses



Storage
facilities

Light source information

- Lifetime 50 000 hours (@L70, Ta 25 °C)
- 2000 lm (20 W), 4000 lm (40 W), 6000 lm (60 W), 8000 lm (80 W), 100 lm/W
- Colour temperature 4000 K
- CRI 80
- MacAdam (initial): 4 step



THORN
eco



Lighting distribution

Lucy 6000 lm

cd/klm ULOR: 0 % DLOR: 100 % LOR: 100 %



Ordering guide

Description	Wt (kg)	SAP Code
LUCY 600 LED IP66 2000 840 TW	0.7	96630331
LUCY 1200 LED IP66 4000 840 TW	1.15	96630332
LUCY 1500 LED IP66 6000 840 TW	1.4	96630333
LUCY 1800 LED IP66 8000 840 TW	1.65	96630334

Installation/Mounting

- Suitable for surface mounting with surface mount brackets (included)
- Mounting brackets can flexibly slide along the full length of the product

Material/Finish

Body: White, polycarbonate
Diffuser: Opal, polycarbonate

Specification

- Class I electrical
- IP66
- IK08
- Ambient operating temperature: -20 to +40 °C

