

# Mike

## Undercabinet LED Batten



### Meet Mike

A reliable and compact LED batten, Mike helps provide an ambient environment

- High quality diffuser ensures uniform light without visible spots
- Can be individual or continuous mounted (16 pcs of 600 mm batten & 8 pcs of 1200 mm batten)
- Supplied complete with starter lead, mounting kit, connector lead and end cap
- Mounting clips can be flexibly attached on the whole length of the batten



900 lm (11W) and 1800 lm (22W), up to 82 lm/W



40% energy savings compared to T5 fluorescent



1200 mm (1800 lm) and 600 mm (900 lm)

#### Ideal for...



Cove lighting



Cabinet lighting



Residential

#### Light source information


- Lifetime 50 000 hours (@L70, Ta 25 °C)
- 900 lm (11W), 1800 lm (22W), 82 lm/W
- Colour temperature 3000K and 4000K
- CRI 80
- MacAdam (initial): 4 step



## Lighting distribution

### Mike 1200 mm 1800 lm

cd/klm ULOR: 23% DLOR: 77% LOR: 100%



## Ordering guide

| Description            | Wt (kg) | SAP Code |
|------------------------|---------|----------|
| MIKE LED 600 900 830   | 0.19    | 96644485 |
| MIKE LED 600 900 840   | 0.19    | 96644486 |
| MIKE LED 1200 1800 830 | 0.32    | 96644483 |
| MIKE LED 1200 1800 840 | 0.32    | 96644484 |
| <b>Spare parts</b>     |         |          |
| MIKE Spare Mount Kit   | 0.06    | 96628411 |

830-3000K, 840-4000K

### Installation/Mounting

- Suitable for surface mounting.
- The fitting can be mounted individually or continuously (16 pcs of 600 mm batten & 8 pcs of 1200 mm batten).

### Material/Finish

Body and diffuser: Dual-color extruded polycarbonate

### Specification

- Class II electrical
- IP20
- IK02

