

# Poppy

## LED Batten



## Meet Poppy

Calm and composed,  
Poppy blends into a wide  
range of indoor settings

- An easy to install and versatile IP20 batten
- Direct replacement for conventional battens in terms of light performance and length
- Reliable integrated LED technology, ensuring maintenance-free installation and a long lifetime
- Homogeneous illumination
- Quick opening and installation thanks to the press release buttons
- Piano-key terminals, enabling loop-in loop-out
- Suspended LED tray for easy installation



2500–8500  
lumens,  
106lm/W



IK08 rated  
impact  
resistance



50 000 hours  
lifetime



Save up  
to 60 %  
compared to  
T8 fluorescent

### Ideal for...



Corridors



Workshops



Warehouses

### Light source information

- 2500lm (24W), 4500lm (40W), 5000lm (48W), 6500lm (60W), 8500lm (80W), 106lm/W
- Lifetime 50 000 hours (@L70, Ta 25°C)
- Colour temperature 4000K
- CRI 80
- MacAdam (initial): 5 step

L

|                         |      |
|-------------------------|------|
| POPPY LED 600 2500 840  | 560  |
| POPPY LED 1200 2500 840 | 1160 |
| POPPY LED 1200 5000 840 | 1160 |
| POPPY LED 1500 4500 840 | 1460 |
| POPPY LED 1500 6500 840 | 1460 |
| POPPY LED 1800 6500 840 | 1722 |
| POPPY LED 1800 8500 840 | 1722 |




## Lighting distribution

### Poppy 6500lm

cd/klm ULOR: 15% DLOR: 85% LOR: 100%

106lm/W



## Ordering guide

| Description                | Wt (kg) | SAP Code |
|----------------------------|---------|----------|
| POPPY LED 600 2500 840     | 1.4     | 96631257 |
| POPPY LED 1200 2500 840    | 2.0     | 96631258 |
| POPPY LED 1200 5000 840    | 2.0     | 96631259 |
| POPPY LED 1500 4500 840    | 3.6     | 96631260 |
| POPPY LED 1500 6500 840    | 3.6     | 96631261 |
| POPPY LED 1800 6500 840    | 4.3     | 96631262 |
| POPPY LED 1800 8500 840    | 4.3     | 96631263 |
| POPPY LED 1200 2500 840 E3 | 2.5     | 96631268 |
| POPPY LED 1200 5000 840 E3 | 2.5     | 96631269 |
| POPPY LED 1500 4500 840 E3 | 4.3     | 96631270 |
| POPPY LED 1500 6500 840 E3 | 4.3     | 96631271 |
| POPPY LED 1800 6500 840 E3 | 5.0     | 96631272 |
| POPPY LED 1800 8500 840 E3 | 5.0     | 96631273 |
| <b>Accessories</b>         |         |          |
| POPPY LED Suspension Kit   | 0.04    | 96631274 |

### Installation/Mounting

- Suitable for surface mounting and suspended installation
- Rear and side entry possible
- BESA fixing points

### Material/Finish

Body: sheet metal, white finish (RAL 9002)  
 Diffuser: polycarbonate, opal  
 End caps: polycarbonate, white (RAL 9002)

### Specification

- Class I electrical
- IP20
- IK08
- ENEC certified driver

### Replacement

| Product                 | Wattage/Output  | Replaces   |
|-------------------------|-----------------|------------|
| POPPY LED 600 2500 840  | 24W LED, 2500lm | 2 x 18W T8 |
| POPPY LED 1200 2500 840 | 24W LED, 2500lm | 1 x 36W T8 |
| POPPY LED 1200 5000 840 | 48W LED 5000lm  | 2 x 36W T8 |
| POPPY LED 1500 4500 840 | 40W LED 4500lm  | 1 x 58W T8 |
| POPPY LED 1500 6500 840 | 60W LED 6500lm  | 2 x 58W T8 |
| POPPY LED 1800 6500 840 | 60W LED 6500lm  | 1 x 70W T8 |
| POPPY LED 1800 8500 840 | 80W LED 8500lm  | 2 x 70W T8 |

