

# Lucy

## LED Batten

Coming soon

### Meet Lucy

Tough, resilient and efficient, Lucy is ideal for workshop areas and functional applications

- High quality, low energy lighting in wet and dusty environments with opal diffuser for uniform lighting
- 2000lm (20W), 4000lm (40W), 6000lm (60W), 100lm/W
- Through-wired: equipped with two 3-pole push-terminals (N, earth, L) as standard
- Easy, quick and tool-free installation thanks to the twist & lock mechanism in the end caps, which allowing access to the push terminals
- Flexible installation as mounting brackets can be positioned freely on the luminaire



**IP66:**  
Dust tight and water resistant



**IK08 rated**  
impact resistance



Save up to 60% compared to T8 fluorescent



600 mm, 1200 mm and 1500 mm



Through-wired



Tool free installation

Ideal for...



Car parks



Workshops



Underpasses



Storage facilities

### Light source information

- Lifetime 50 000 hours (@L70, Ta 25 °C)
- 2000lm (20W), 4000lm (40W), 6000lm (60W), 100lm/W
- Colour temperature 4000K
- CRI 80
- MacAdam (initial): 4 step




## Lighting distribution

### Lucy 6000 lm

cd/klm ULOR: 0 % DLOR: 100 % LOR: 100 %

100 lm/W



### Installation/Mounting

- Suitable for surface mounting with surface mount brackets (included)
- Mounting brackets can flexibly slide along the full length of the product

### Material/Finish

Body: White, polycarbonate  
Diffuser: Opal, polycarbonate

### Specification

- Class I electrical
- IP66
- IK08

## Ordering guide

| Description                    | Wt (kg) | SAP Code |
|--------------------------------|---------|----------|
| LUCY 600 LED IP66 2000 840 TW  | 0.7     | 96630331 |
| LUCY 1200 LED IP66 4000 840 TW | 1.15    | 96630332 |
| LUCY 1500 LED IP66 6000 840 TW | 1.4     | 96630333 |

