

Mike

Undercabinet LED Batten



Meet Mike

A reliable and compact LED batten, Mike helps provide an ambient environment

- High quality diffuser ensures uniform light without visible spots
- Can be individual or continuous mounted (16 pcs of 600mm batten & 8 pcs of 1200mm batten)
- Supplied complete with starter lead, mounting kit, connector lead and end cap
- Mounting clips can be flexibly attached on the whole length of the batten



900 lm (11W) and 1800 lm (22W), up to 82 lm/W



40% energy savings compared to T5 fluorescent



1200 mm (1800 lm) and 600 mm (900 lm)

Ideal for...



Cove lighting



Cabinet lighting



Residential

Light source information



- Lifetime 50 000 hours (@L70B50, Ta 25 °C)
- 900 lm (11W), 1800 lm (22W), 82 lm/W
- Colour temperature 3000K and 4000K
- CRI 80
- McAdams (initial): 4 step



Lighting distribution

Mike 1200 mm 1800 lm

cd/klm ULOR: 23 % DLOR: 77 % LOR: 100 %



Ordering guide

Description	Wt (kg)	Cat. No.
MIKE LED 600 900 830	0.17	MI900Z3K2F
MIKE LED 600 900 840	0.17	MI900Z4K2F
MIKE LED 1200 1800 830	0.29	MI1800Z3K4F
MIKE LED 1200 1800 840	0.29	MI1800Z4K4F
Spare part		
MIKE Spare Mount Kit		MIACCKIT
830-3000K, 840-4000K		

Installation/Mounting

- Suitable for surface mounting.
- The fitting can be mounted individually or continuously (16 pcs of 600mm batten & 8 pcs of 1200mm batten)

Material/Finish

Body and diffuser: Dual-color extruded polycarbonate

Specification

- Class II electrical
- IP20
- IK02

