

Chloe Vario

LED Downlight



Meet Chloe Vario

Versatile and durable,
Chloe Vario blends
in a wide range of
applications

- A slim ceiling recessed LED downlight with switchable light colour: choose between warm white (3000 K), cool white (4200 K) and daylight (5700 K) to suit application use
- Beam angle 95°
- High colour rendering and uniform light surface with no shadowing
- External electronic: dimmable LED driver suitable with trailing edge and universal dimmers*
- Thermally optimised aluminium body
- Fitted with flex and plug
- Interchangeable trim rings available separately

*see installation instructions for compatible dimmer list



800 - 945
lumens, up
to 94.5lm/W



30 000 hours
lifetime



Switchable
light colour



IP44
(from below)
IP20
(from above)



Replacement
for 1 x 18 W CFL



Dimmable

Ideal for...



Corridors



Reception areas



Offices and meeting rooms






Schools and universities

Light source information

- Lifetime 30 000 hours (L70, Ta 25 °C)
- 3000 K: 800lm (10 W), 80 lm/W
- 4200 K: 945lm (10 W), 94.5 lm/W
- 5700 K: 890lm (10 W), 89 lm/W
- CRI 80



IC-4




Lighting distribution

Chloe Vario 850 lm

cd/klm ULOR: 0 % DLOR: 100 % LOR: 100 %

85 lm/W



Ordering guide

Description	Wt (kg)	SAP Code
CHLOE VAR LED 90 800 830/42/57 DIM WH FP	0.55	96631233
CHLOE VAR TRIM WH FLAT	0.03	96631234
CHLOE VAR TRIM SR REBATED	0.05	96631235
CHLOE VAR TRIM SR FLAT	0.03	96631236
CHLOE VAR TRIM BK REBATED	0.05	96631237
CHLOE VAR TRIM BK FLAT	0.03	96631238

Installation/Mounting

- Chloe Vario LED can be installed into a wide range of ceiling types of 2–20 mm thickness

Material/Finish

Body: Aluminium
Trim: Metal, white

Specification

- Class II electrical
- IP44 (from below), IP20 (from above)
- IK02
- Insulation Coverable Luminaire and Driver (IC-4/IC-F)



96631238



96631234



96631236



96631237



included with the product



96631235

