Bright Heroes

Emergency Lighting Trio



Reliable and always ready, our bright heroes will guide you through the dark

- Automatic self-tests to ensure functionality
- Based on the latest technology with lithium iron phosphate battery (LiFePO4) for 3 h emergency operation
- Three year guarantee on battery



ANTIPANIC ESCAPE

Iris - SelfTest Emergency Downlight

- Two light distributions available: ANTIPANIC and ESCAPE
- Optimised for large spacing
- Optional box for surface mounting

Nina - SelfTest Exit Sign

- 4 Pictograms included: Left, Right, Up, Down
- Operation mode: maintained or non maintained
- Mounting on Ceiling or Wall, 90°
- Viewing range 30 m

Sam - SelfTest Emergency Bulkhead

- 4 Pictograms included: Left, Right, Arrow, Blank
- Operation mode: maintained or non-maintained
- Mounting on Ceiling or Wall, 90°
- IP65 and IK08
- Viewing range 20 m

THORN

Iris:



Surface Mount Box:



Nina:



Sam:



Facilitating life

Iris – Choose between two light distributions to add maximum safety even within a large space

Light distribution ANTIPANIC
For antipanic general illumination with min 0.5 lx

Light distribution ESCAPE
For escape route lighting with min 1 lx

Nina and Sam – you will definitely see them!



Ordering guide

Description	Code SAP
Iris - SelfTest Emergency Downlight	
IRIS ANTIPANIC SELFTEST E3 LiFePO4	96635650
IRIS ESCAPE SELFTEST E3 LiFePO4	96635651
IRIS SURFACE MOUNT BOX	96635652
IRIS REPLACEMENT BATTERY LiFePO4	96635653
Nina - SelfTest Exit Sign	
NINA 30M SELFTEST E3 LiFePO4	96635654
NINA REPLACEMENT BATTERY LiFePO4	96635655
Sam - SelfTest Emergency Bulkhead	
SAM 20M SELFTEST E3 LiFePO4	96635656
SAM REPLACEMENT BATTERY LiFePO4	96635657

All products with with SelfTest and for 3 h emergency operation

Planning recommendation

	Iris - Self Test Emergency Downlight				Sam - Self Test Emergency Bulkhead			
	ANTIPANIC – 0.5 lx		ESCAPE – 1 lx		0.5 lx		1 lx	
								
2.0 m	5.8	14.2	6.6	14.9	3.5	8.8	2.8	7.1
2.5 m	5.6	15.8	7.4	17.3	3.8	9.6	2.9	7.6
3.0 m	4.6	16.5	7.8	19.4	4.0	10.3	3.0	8.0
3.5 m	4.4	15.9	7.6	20.9	4.1	10.8	3.0	8.3
4.0 m	4.3	13.6	7.0	21.9	4.2	11.2	2.9	8.5
4.5 m	4.0	12.8	6.6	22.1	4.3	11.6	2.7	8.6

5 Five year guarantee