


Julie Vario

IP65 LED Luminaire



With a tough exterior, Julie is the optimal choice for industrial and commercial applications

- Switchable light colour: choose between warm white (3000K), cool white (4000K) or daylight (5700K) to suit the application
- High quality, low energy lighting in wet and dusty environments
- High quality opal diffuser for uniform lighting
- Ideal for replacement and refurbishment projects, saving up to 60% energy compared to T8 fluorescent
- 2200lm (19W), 4200lm (38W), 6300lm (55W), up to 116lm/W
- Versions with presence sensor and corridor function



Switchable light colour



IP65:
Dust tight and water resistant



IK08 rated impact resistance



Lengths of 632, 1232 and 1532 mm



2h emergency version available



Presence sensor with corridor function

Ideal for ...



Workshops



Underpasses



Storage facilities



Specification

- Class I electrical
- IK08
- IP65
- Ambient operating temperature: -20 to +40°C (E2: 0 to +25°C)



JULIE VAR LED 600 2200 830/40/57
JULIE VAR LED 1200 4200 830/40/57
JULIE VAR LED 1500 6300 830/40/57

L	W	H
632	103	78
1232	85	71
1532	103	78




Lighting distribution

111lm/W



Julie Vario LED 4200 lm

cd/klm ULOR: 8 %
DLOR: 92 %
LOR: 100 %



Presence sensor with corridor function

Julie's microwave sensor option with corridor function will ensure that you never walk in the dark. The settings are fully adjustable, with the additional benefit of a daylight sensor.

Light source information

- Lifetime 50 000 hours (@L70, Ta 25 °C)
- 2200lm (19W), 4200lm (38W), 6300lm (55W), up to 116lm/W
- Colour temperature 3000K, 4000K and 5700K in one product
- CRI80
- MacAdam (initial): 4 step

Installation/Mounting

- Suitable for surface mounting

Material/Finish

Canopy: Polycarbonate
Diffuser: Opal polycarbonate (UV stabilised)
Bracket: Stainless steel



Ordering guide

Description	Wt (kg)	SAP Code
JULIE VAR LED 600 2200 830/40/57	1.03	96649388
JULIE VAR LED 1200 4200 830/40/57	1.50	96649389
JULIE VAR LED 1500 6300 830/40/57	1.95	96649390
JULIE VAR LED 600 2200 830/40/57 MWSCOR	1.95	96649391
JULIE VAR LED 1200 4200 830/40/57 MWSCOR	2.05	96649392
JULIE VAR LED 1500 6300 830/40/57 MWSCOR	2.35	96649393
Emergency versions		
JULIE VAR LED 600 2200 830/40/57 E2	2.00	96649394
JULIE VAR LED 1200 4200 830/40/57 E2	2.15	96649395
JULIE VAR LED 1500 6300 830/40/57 E2	2.20	96649396
JULIE VARLED600 2200 830/40/57 MWSCOR E2	2.60	96649397
JULIE VARLED1200 4200 830/40/57 MWSCOR E2	2.65	96649398
JULIE VARLED1500 6300 830/40/57 MWSCOR E2	3.05	96649399
Spare parts		
JULIE LED Spare Mount Kit	0.10	96628409

MWS: microwave presence sensor COR: corridor function

Sensor Range

at 100% sensitivity



Controllability

Sensitivity	50%, 100%
Time	5s, 30s, 1min, 10min
lux	2lux, 10lux, 50lux, disable
Stand-by time	0sec, 30sec, 20min, endless
Dimming Level	10%, 20%, 30%, 50%

