


Tom

IP66 Bulkhead

VARIO FLEX





Ideal for: Circulation corridors, public entrance areas, stairwells, sanitary rooms and underpasses

Comfortable, flexible and variable both indoors and outdoors




- **VARIO Feature (Colour Temperature Switch):** The ability to choose five different colour temperature on site with the flick of a switch
- **FLEX Feature (Lumen Output Switch):** The flexibility to decide on four lumen packages on site with the flick of a switch
- **Screwless, tamperproof design** prevents vandalism by being visually free from access points
- **Robust construction up to IK10 impact resistance**
- **Centred cable entry points** makes it easier to install on a level
- **Maximise energy savings** using microwave sensor and corridor function (available as options)
- **Replaceable light engine and driver** extend the life of the product
- **JUST – adapt on-site to an emergency version** using the Just Emergency Plug&Play kit



	Ø	H
TOM	313	79

Dimensions (mm)



Specification

Electrical class	II
Ambient operating temperature	-20°C - +40°C
Driver	ENEC

Installation / Mounting

Mounting	Wall, Ceiling, Interior, Outdoor
Installation	Tool free

Material / Finish

Body	UV Stabilised PC
Diffuser	UV Stabilised PC

Light source information


VARIO (Colour temperature switch)	3000 K, 3500 K, 4000 K, 5700 K, 6500 K
FLEX (Lumen switch)	800lm(7.5W), 1200lm(11W), 1800lm(16W), 2200lm(20W)
Efficiency	110lm/W
Lifetime	50 000 hours (@L80, Ta 25 °C)
MacAdam (Initial)	<5

Controllability (MWS) (default)

Sensitivity	100%, 75%, 50%, 25%, 10%
Time	30min, 20min, 3min, 90s, 30s, 5s
Switching Load	400W
Lux	50Lux, 25Lux, 10Lux, 2Lux, Disable

Sensor range

at 100 % sensitivity



	h1	d1	h2	d2
100 %	4m	10m	8m	8m
50 %	3m	8m	6m	7m

Ordering guide

Description	SAP Code
TOM VF 2200 830/35/40/57/65 WH	96637988
TOM VF 2200 830/35/40/57/65 WH MWS	96637989
TOM VF 2200 830/35/40/57/65 WH MWSCOR	96637990
Accessories	
JUST E3/E3T CIR LIFEPO4 F1	96638038
DRV TE TOM VF/LARA VF2 V1*	59013727
DRV TE TOM VF/LARA VF2 MWSCOR V1**	59013728
LE TE TOM VF/LARA VF2 V1	59013729

MWS: microwave presence sensor.

MWSCOR: microwave presence sensor with corridor function

DRV: spare driver

LE: light engine

WH: white

* suitable for use with 96637988 & 96638989


** suitable for use with 96637990

Controllability (MWS COR) (default)

Sensitivity	100% / 50%
Time	5 s (testing) / 5 min / 15 min / 30 min
Stand by level	10 %
Stand by time	0 s / 5 min / 15 min / never off
Daylight Sensor	OFF: MWS only
	5 on / 7,5 off lux: external pedestrian walkway
	100 on / 150 off lux: Internal Circulation Areas (corridors and stairs), Stockrooms and Storerooms
	200 on / 300 off lux: Internal Washrooms, Toilets and Cloakrooms
Mode	Microwave Sensor + Daylight / Photocell only

Sensor range

at 100 % sensitivity



	h1	d1	h2	d2
100 %	3m	10m	2m	6m
50 %	3m	6m	2m	3m